

## LISTING OF CLAIMS

Please amend claims 1, 2, 7-9, 12, 13, 27 and 28, and cancel claims 22-26 and 40, as shown in the Listing of Claims below. This Listing of Claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A method for removing non-condensing gas from a mixture of condensing and non-condensing gases in a condenser, wherein gas is withdrawn from at least one location within the condenser to reduce the mass fraction of non-condensing gas immediately adjacent a cooling surface, the location being selected to correspond to a region within the condenser in which the gas is at a temperature which is lower than the temperature of gas in other regions within the condenser ~~and adjacent to condensate formed from the condensing gas~~.
2. (currently amended) A condenser for condensing gas ~~in which gas is condensed to liquid on a heat exchanging surface~~, the condenser comprising:  
a heat exchanging surface for condensing a condensing gas to a liquid; and  
means for withdrawing non-condensing gas from within the condenser ~~to remove non-condensing gas~~, the gas withdrawing means being positioned to withdraw non-condensing gas from at least one location in which the gas temperature is lower than in other regions within the condenser ~~and adjacent to condensate formed from the condensing gas~~ thereby to reduce the mass fraction of non-condensing gas immediately adjacent the heat exchanging surface.
3. (original) A condenser according to claim 2, wherein the gas withdrawing means comprises cooling means for producing a localised region of relatively cold gas in the location from which gas is withdrawn.
4. (original) A condenser according to claim 3, wherein the cooling means comprise a heat exchanger on which gas condenses.

5. (previously presented) A condenser according to claim 3 wherein the cooling means comprises means positioned to be cooled by condensing liquid.
6. (original) A condenser according to claim 5, wherein the cooling means comprises at least one deflector located beneath the heat exchanging surface such that droplets of liquid fall onto and cool the deflector, the gas withdrawing means extracting air from beneath the deflector.
7. (currently amended) A condenser according to claim 6, wherein ~~the or each deflector is~~ said at least one deflector comprises a cover extending over an upwardly extending gas withdrawal pipe.
8. (currently amended) A condenser according to claim 6, wherein ~~the or each deflector is~~ said at least one deflector comprises an elongate gas withdrawal duct a lower side of which defines apertures through which gas is withdrawn into the elongate duct.
9. (currently amended) A condenser according to claim 6, wherein ~~the or each deflector is~~ said at least one deflector comprises an elongate duct an underside of which defines an open channel, the gas withdrawing means being connected to one end of the elongate duct.
10. (previously presented) A condenser according to claim 8 wherein the elongate duct extends beneath and in parallel with a heat exchanger tube of the condenser.
11. (previously presented) A condenser according to claim 6 wherein a shield is located above the or each deflector to shield falling droplets of condensate from gas flowing through the condenser.

12. (currently amended) A condenser according to claim 3, wherein the cooling means comprises a surface which is configured to be cooled by a flow of coolant.

13. (currently amended) A condenser according to claim 12, wherein the surface of the cooling means is configured to be cooled by a flow of coolant to a temperature lower than any heat exchange surface within the condenser.

14. (original) A condenser according to claim 12, wherein the cooling means comprises primary and secondary heat exchangers both defining heat exchange surfaces, the heat exchange surface of the primary heat exchanger being located upstream of the heat exchange surface of the secondary heat exchanger in the flow of gas to be condensed, and the secondary heat exchanger being cooled to a lower temperature than the primary heat exchanger.

15. (original) A condenser according to claim 14, wherein the primary and secondary heat exchangers are cooled by flows of coolant derived from separate sources, the coolant of the secondary heat exchanger being at a lower temperature than the coolant of the first heat exchanger.

16. (previously presented) A condenser according to claim 2 comprising an auxiliary heat exchanger within the condenser, and means for pumping condensed liquid through the auxiliary heat exchanger, the auxiliary heat exchanger being located such that the condensed liquid within it is heated by the gas to be condensed.

17. (original) A condenser according to claim 16, wherein the auxiliary heat exchanger is located upstream of the said heat exchanging surface in the flow of gas to be condensed.

18. (original) A condenser according to claim 12, wherein the cooled surface is defined by a pool of condensed liquid in thermal contact with a cooling device.

19. (original) A condenser according to claim 12, wherein the cooled surface is defined by a wall of the condenser in thermal contact with a cooling device.

20. (original) A condenser according to claim 19, wherein the condenser wall is defined by a cover plate which covers an aperture in the condenser, gas being withdrawn through the cover plate.

21. (original) A condenser according to claim 20, comprising means for monitoring the pressure and temperature of gas adjacent the cover plate, and means for controlling the cooling means to maintain the temperature of the cover plate above the freezing point of the condensed liquid.

22-26. (canceled)

27. (currently amended) A method for minimizing the pressure within a containment vessel resulting from the release into the vessel of a pressurized gas which will condense to a liquid at the temperatures and pressures assumed to prevail within the containment vessel, wherein a body of the liquid of large surface area relative to the area of the vessel is established provided in a lower portion of the vessel to establish a coolant effective for producing a localized region of non-condensing gas adjacent the coolant and thereby reduce the mass fraction of non-condensing gas in an upper portion of the vessel.

28. (currently amended) A containment vessel ~~intended to contain~~ effective for containing a release into the vessel of pressurized gas which will condense to a liquid at the temperatures and pressures assumed to prevail within the containment vessel, the containment vessel initially being filled with a gas or gases which will not condense at

the temperatures and pressures assumed to prevail within the containment vessel, and the containment vessel including means a body of liquid of large surface area relative to the area of the vessel for establishing a coolant in a lower portion of the vessel ~~a body of the liquid of large surface area relative to the area~~ so as to produce a localized region of non-condensing gas adjacent the coolant and thereby to reduce the mass fraction of non-condensing gas in an upper portion of the vessel.

29. (original) The containment vessel according to claim 28, comprising at least one open tray arranged to collect condensing liquid to form the said body of liquid.

30. (original) A containment vessel according to claim 28, comprising means for releasing a stored volume of the liquid into at least one open tray to form the said body of liquid.

31. (original) A containment vessel according to claim 30, comprising means for sensing pressure within the containment vessel, and means for releasing the stored volume of liquid in the event of the sensed pressure exceeding a predetermined threshold.

32 – 37. (cancelled)

38. (previously presented) A method for reducing the concentration of non-condensing gas from a mixture of condensing and non-condensing gases in a condenser, comprising:

- providing a condenser to cool a mixture which includes a condensing gas and a non-condensing gas;

- flowing the mixture within the condenser;

- cooling the flowing mixture in the condenser;

- providing at least one region of relative low mixture temperature within the condenser, the region having relative high concentration of the non-condensing gas;

forming condensate in the condenser proximate to said region; and  
withdrawing gas from said region to reduce the overall concentration of the non-condensing gas in the condenser.

39. (previously presented) An apparatus for condensing gas to liquid, comprising:  
a condenser for removing heat from a gas, said condenser having an interior with at least one region of relative low temperature during operation of said condenser, said region being proximate formed condensate during operation of said condenser; and  
means for withdrawing gas from said region of said condenser to reduce the concentration of a non-condensing gas in the condenser.

40. (canceled)

41. (previously presented) A method for enhancing the loss of heat from a mixture of gases to a surrounding containment vessel to condense liquid from the gas to limit its pressure, comprising:

providing a containment vessel having an interior and an internal surface area, the containment vessel containing a non-condensing gas and surrounding an apparatus containing a heated and pressurized process fluid;

after a portion of the process fluid is released into the interior of the containment vessel to produce a mixture of condensing and non-condensing gas in the containment vessel, enhancing the loss of heat to the containment vessel to promote cooling of the condensing gas to produce a quantity of condensate and limit the pressure within the containment vessel; and

collecting the condensate in one or more pools within a lower portion of the containment vessel, the collected condensate having a surface area, the surface area of the condensate being large relative to the internal surface area of the containment vessel.